

STANAG 4569									
Protection level	Threat	Velocity (m/s)	Range (m)	Armox 500 (mm)	Armox 600 (mm)	Armox Advance (mm)	Ramor 500 (mm)	Ramor 550 (mm)	Ramor 600 (mm)
Level 1	5,56x45 SS109	900±20							
	5,56x45 M193	937±20	30	9	6	5	9.2	8.1	-
	7,62x51 Ball	833±20							
Level 2	7,62x39 API BZ	695±20	30	12	8.5	7	12.2	10.1	-
Level 3	7,62x54R B32 API	854±20	30	22	21	-	-	-	-
	7,62x51 AP (WC)	930±20							

EN 1522									
Protection level	Threat	Velocity (m/s)	Range (m)	Armox 500 (mm)	Armox 600 (mm)	Armox Advance (mm)	Ramor 500 (mm)	Ramor 550 (mm)	Ramor 600 (mm)
FB4	.357 Mag FJ/CB/SC	430±10	5	-	-	-	2.5	-	-
	.44 Mag FJ/FN/SC	440±10							
FB4+	7.62x39 M43	700±10	10	4.0	-	-	4.0	3.7	3.5
FB5	5,56x45 SS109	950±10	10	6.5	5	4.5	6.5	5.9	5.0
FB6	5,56x45 SS109	950±10	10	6.5	5	4.5	6.5	5.9	5.0
	7,62x51 NATO Ball	830±10							
FB7	7,62x51 NATO AP	820±10	10	14.5	12	9	14.5	13.1	-

NIJ									
Protection level	Threat	Velocity (m/s)	Range (m)	Armox 500 (mm)	Armox 600 (mm)	Armox Advance (mm)	Ramor 500 (mm)	Ramor 550 (mm)	Ramor 600 (mm)
II	9mm FMJ	367±9	5	3	-	-	2.2	-	-
	.357 Magnum JSP	436±9							
IIIA	9mm FMJ	436±9	5	3	-	-	2.5	-	-
	.44 Magnum JHP	436±9							
III	7,62x51 NATO Ball	838±9	15	6.5	5.0	5.0	6.0	5.7	5.0
IV	.30 M2AP		15	14	10	9	14	13	-

VPAM PM 2007 / PREFERRED CIVILIAN STANDARD									
Protection level	Threat	Velocity (m/s)	Range (m)	Armox 500 (mm)	Armox 600 (mm)	Armox Advance (mm)	Ramor 500 (mm)	Ramor 550 (mm)	Ramor 600 (mm)
PM4	.357 Mag FJ/CB/SC	430±10	5	-	-	-	2.5 normal	3.0	-
	.44 Mag FJ/FN/SC	440±10					multihit		
PM6	7.62x39 M43	720±10	10	-	-	-	4.25 multihit	3.7 normal	3.5 normal
PM7	5,56x45 SS109	950±10	10	6.5	5	5	6.5 multihit	5.9 normal	5.0 normal
	7,62x51 NATO Ball	830±10							
PM9	7,62x51 NATO AP	820±10	10	14.5	12	9	14.5	13.1	-